

SAFETY DATA SHEET

ULTRADENT[®]
PRODUCTS, INC.

Date Issued: 02/09/2006
MSDS No: 22-001.4
Date-Revised: 11/16/2010
Revision No: 3

UltraTemp[®] Catalyst

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME: UltraTemp[®] Catalyst

PRODUCT DESCRIPTION: Clear gel used to accelerate UltraTemp luting and filling material

MANUFACTURER

Ultradent Products, Inc.
505 W. 10200 S.
South Jordan, UT 84095

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (NORTH AMERICA) :(800) 424 - 9300
(INTERNATIONAL) :+1(703) 527 - 3887

2. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS	EINECS	Classification	Content
Poly (Acrylic Acid)	9003-01-4		Xi; R36/37/38	46
Benzoic Acid	65-85-0	200-618-2	Xi; R36/37/38	15

(Full text of R-Phrases can be found under heading 16)

3. HAZARDS IDENTIFICATION

HAZARD DESIGNATION

"Xi" - Irritant

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: No adverse human effects

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

SKIN: Wash with soap and water.

INGESTION: If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

5. FIRE FIGHTING MEASURES

FIRE FIGHTING PROCEDURES: General: Evacuate all personnel; use protective equipment for fire-fighting. Use self-contained breathing apparatus when the product is involved in fire.

FIRE FIGHTING EQUIPMENT: Water spray, fog, or mist, foam, dry chemical, carbon dioxide.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Wipe up with cloth, soap, and water.

LARGE SPILL: Absorb with inert, damp non-combustible material, then flush area with water.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Do not allow to enter sewers or drains that may lead to waterways.

7. HANDLING AND STORAGE



SAFETY DATA SHEET

Date Issued: 02/09/2006
MSDS No: 22-001.4
Date-Revised: 11/16/2010
Revision No: 3

UltraTemp® Catalyst

HANDLING: Use suitable protective equipment.

STORAGE: Store in a cool dry place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear eye protection.

SKIN: S36/37: Wear suitable protective clothing and gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Gel

ODOR: Pungent, typical acrylic acid odor.

COLOR: Colorless to slight yellow

10. STABILITY AND REACTIVITY

STABLE: Yes

11. TOXICOLOGICAL INFORMATION

EYE EFFECTS: May cause mild irritation.

SKIN EFFECTS: May cause slight irritation.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of in compliance with governmental and local regulations.

14. TRANSPORT INFORMATION

ROAD AND RAIL (ADR/RID)

LABEL: Not classified

AIR (ICAO/IATA)

LABEL: Not classified

VESSEL (IMO/IMDG)

LABEL: Not classified

15. REGULATORY INFORMATION

EUROPEAN COMMUNITY

SAFETY DATA SHEET

ULTRADENT[®]
PRODUCTS, INC.

Date Issued: 02/09/2006
MSDS No: 22-001.4
Date-Revised: 11/16/2010
Revision No: 3

UltraTemp[®] Catalyst

EEC LABEL SYMBOL AND CLASSIFICATION



"Xi" - Irritant
S37/39: Wear suitable gloves and eye/face protection.

16. OTHER INFORMATION

RELEVANT R-PHRASES: R36/37/38: Irritating to eyes, respiratory system and skin.

PREPARED BY: Susan Scott

REVISION SUMMARY: Revision #: 3. This MSDS replaces the November 16, 2010 MSDS. Any changes in information are as follows: In Section 1: MSDS Number, Prepared By

MANUFACTURER DISCLAIMER: FOR DENTAL USE ONLY: Use as directed.

The information and recommendations are taken from sources (raw material MSDS(s) and manufacturer's knowledge) believed to be accurate; however, Ultradent Products, Inc., makes no warranty with respect to the accuracy of the information or the suitability of the recommendation and assumes no liability to any user thereof. Each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.