

SAFETY DATA SHEET

ULTRADENT[®]
PRODUCTS, INC.

Date Issued: 11/17/2006
MSDS No: 70-001.6
Date-Revised: 07/18/2008
Revision No: 5

Peak[™] Bond

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME: Peak[™] Bond
PRODUCT DESCRIPTION: Dental bonding resin
PRODUCT CODE: BK

MANUFACTURER

Ultradent Products, Inc.
505 W. 10200 S.
South Jordan UT 84095

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (NORTH AMERICA) :(800) 424 - 9300
(INTERNATIONAL) :+1(703) 527 - 3887

2. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS	EINECS	Classification	Content
Ethyl alcohol	000064-17-5	200-578-6	F+; R11	17
2-hydroxyethyl Methacrylate	000868-77-9	212-782-2	Xi; R43	16

(Full text of R-Phrases can be found under heading 16)

3. HAZARDS IDENTIFICATION

HAZARD DESIGNATION

"F" - Highly flammable
R11: Highly flammable.
"Xi" - Irritant
R43: May cause sensitization by skin contact.

POTENTIAL HEALTH EFFECTS

EYES: Can cause severe eye irritation.
SKIN: May cause skin irritation.

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

SKIN: Wash with soap and water. Get medical attention if irritation develops or persists.

INGESTION: If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

5. FIRE FIGHTING MEASURES

SAFETY DATA SHEET

ULTRADENT[®]
PRODUCTS, INC.

Date Issued: 11/17/2006
MSDS No: 70-001.6
Date-Revised: 07/18/2008
Revision No: 5

Peak[™] Bond

FIRE FIGHTING PROCEDURES: General: Evacuate all personnel; use protective equipment for fire-fighting. Use self-contained breathing apparatus when the product is involved in fire.

FIRE FIGHTING EQUIPMENT: Foam, dry chemical, carbon dioxide (CO₂)

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Absorb liquid and place in sealed container for disposal. Vapors can travel to an ignition source.

LARGE SPILL: Absorb with inert, damp non-combustible material, then flush area with water.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Do not allow to enter sewers or drains that may lead to waterways.

7. HANDLING AND STORAGE

HANDLING: Keep away from heat, sparks and flame.

STORAGE: Keep refrigerated.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear eye protection.

SKIN: S36/37: Wear suitable protective clothing and gloves.

RESPIRATORY: S51: Use only in well-ventilated areas.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Acrylic, pungent

APPEARANCE: Light yellow opaque resin.

10. STABILITY AND REACTIVITY

STABILITY: Stable when stored and handled under recommended conditions.

POLYMERIZATION: Polymerization occurs when exposed to visible light, ultraviolet light or extreme heat.

CONDITIONS TO AVOID: Avoid light exposure.

11. TOXICOLOGICAL INFORMATION

EYE EFFECTS: May cause serious damage.

SKIN EFFECTS: May cause slight irritation.

SAFETY DATA SHEET

ULTRADENT[®]
PRODUCTS, INC.

Date Issued: 11/17/2006
MSDS No: 70-001.6
Date-Revised: 07/18/2008
Revision No: 5

Peak[™] Bond

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: Stable when stored and handled under recommended conditions.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of in compliance with governmental regulation (EC 1975L0442-20/11/2003)

14. TRANSPORT INFORMATION

ROAD AND RAIL (ADR/RID)

PROPER SHIPPING NAME: Alcohols, n.o.s. (Ethyl alcohol mixture)

HAZARD CLASS: 3

PACKING GROUP: III

AIR (ICAO/IATA)

SHIPPING NAME: Alcohols, n.o.s. (Ethyl alcohol mixture)

UN/NA NUMBER: 1987

PRIMARY HAZARD CLASS/DIVISION: 3

PACKING GROUP: III

VESSEL (IMO/IMDG)

SHIPPING NAME: Alcohols, n.o.s. (Ethyl alcohol mixture)

UN/NA NUMBER: 1987

PRIMARY HAZARD CLASS/DIVISION: 3

PACKING GROUP: III

LIMITED QUANTITY: 10 L

15. REGULATORY INFORMATION

EUROPEAN COMMUNITY

EEC LABEL SYMBOL AND CLASSIFICATION



"F" - Highly flammable
R11: Highly flammable.



"Xi" - Irritant
R43: May cause sensitization by skin contact.

16. OTHER INFORMATION

SAFETY DATA SHEET

ULTRADENT[®]
PRODUCTS, INC.

Date Issued: 11/17/2006

MSDS No: 70-001.6

Date-Revised: 07/18/2008

Revision No: 5

Peak[™] Bond

RELEVANT R-PHRASES:

R11: Highly flammable.

R43: May cause sensitization by skin contact.

PREPARED BY: Iris McCallister

REVISION SUMMARY: Revision #: 5. This MSDS replaces the April 22, 2008 MSDS., Any changes in information are as follows: In Section 1: MSDS Number In Section 15: EEC Symbol Id., EEC Risk Phrase Codes

MANUFACTURER DISCLAIMER: FOR DENTAL USE ONLY: Use as directed.

The information and recommendations are taken from sources (raw material MSDS(s) and manufacturer's knowledge) believed to be accurate; however, Ultradent Products, Inc., makes no warranty with respect to the accuracy of the information or the suitability of the recommendation and assumes no liability to any user thereof. Each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.